

FORM PTO-1500 (REV. 12-28-99)		U.S. DEPARTMENT OF COMMERCE, PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			U.S. APPLICATION NO. (If known, see 37 CFR 1.5) 09/509377
INTERNATIONAL APPLICATION NO. PCT/IV 98/00006	INTERNATIONAL FILING DATE October 2, 1998	PRIORITY DATE CLAIMED October 3, 1997	
TITLE OF INVENTION Endoscope with single-use cartridge for the invagination of endoscopic tube			
APPLICANT(S) FOR DO/EO/US Sergey Matasov, Andrei Motasov, Vita Matasova			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
<ol style="list-style-type: none"> 1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). 4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) <ol style="list-style-type: none"> a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). 7. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) <ol style="list-style-type: none"> a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. <input checked="" type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). 			
Items 11. to 16. below concern document(s) or information included:			
<ol style="list-style-type: none"> 11. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. <input type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 14. <input type="checkbox"/> A substitute specification. 15. <input type="checkbox"/> A change of power of attorney and/or address letter. 16. <input checked="" type="checkbox"/> Other items or information: <ol style="list-style-type: none"> 1. Certified copy of priority application P-97-190 2. Certified copy of priority application P-98-188 3. Copy of the author certificate № 1522466 4. Copy of the International Preliminary Examination Report 			

Form PTO-1390 (REV 12-29-99) page 2 of 2

**STATEMENT CLAIMING SMALL ENTITY STATUS
 (37 CFR 1.9(f) & 1.27(b))--INDEPENDENT INVENTOR**

Docket Number (Optional)

Applicant, Patentee, or Identifier: Sergey Matasov

Application or Patent No.: PCT/LV 98/00006

Filed or Issued: October 2, 1998

Title: Endoscope with single-use cartridge for the invagination of endoscopic tube

As a below named inventor, I hereby state that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees to the Patent and Trademark Office described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

I have not assigned, granted, conveyed, or licensed, and am under no obligation under contract or law to assign, grant, convey, or license, any rights in the invention to any person who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ No such person, concern, or organization exists.
☐ Each such person, concern, or organization is listed below

Separate statements are required from each named person, concern, or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

Sergey Matasov
 NAME OF INVENTOR

NAME OF INVENTOR

NAME OF INVENTOR

Signature of inventor

Signature of inventor

Signature of inventor

March 20, 2000

Date

Date

Date

Endoscope
with disposable cartridge for the invagination of endoscopic tube

Description of invention

The invention pertains to the field of medicine, namely to colonoscopy and enteroscopy, but can also be used for industrial endoscopes.

Is known the device under FGR patent No. 3329176, which includes an endoscopic tube, encased in an eversible elastic thin-walled tube which functions as a transporter-invaginator (hereinafter - invaginator) of the first tube. The invaginator in the device patented in FGR is set in long layers parallel to the transported tube. To the drawbacks of this device pertains the inconsequential unreeling of invaginator's layers which is explained by their "sticking together" due to air pressure and inevitable getting of air into spaces between them. Untimely everting of any layer excludes from participation in intubation process other layers located above the everted one.

Is known also the intestinal endoscope under the USSR author's certificate No. 1522466 with an invaginator set in short layers and placed at the right angle with an endoscopic tube, which is transported by it. This endoscope is set as a basis to the present invention and will be taken as a prototype. Endoscope-prototype comprise: - source of light; - source 5 of excessive pressure; - endoscopic tube 3 with eyepiece 1, control block 2 with communication branch, stop 11 for spring 10; - invaginator of endoscopic tube 3 which consists of everted part 4 and uneverted part, encased in part 4, at that, the uneverted part of invaginator tightly adjoins to an endoscopic tube and is placed in short layers perpendicularly to it. From the side of uneverted end 7 the invaginator is supported with spring 10, but the place of transition of uneverted part of the invaginator into everted 4 is limited by tip 6. Besides, the endoscope-prototype has: - external seal 13 of tube 3 on which the end 12 of the everted part 4 of invaginator is fixed with ring 16; - rings 8, 9 on the uneverted end 7 of the invaginator; - air-duct 15 with cock 17 for feeding working pressure into cavity 14 of everted part 4 of the invaginator; anal dilator 19. Apart from light and image transmission elements, biopsy channels, channels for gas or liquid supply, an endoscopic tube 3 of the prototype comprises two pairs of closely wound springs containing traction lines which pairwise connects the distal ring of a mechanism for bending the distal end of a tube and rollers for manual extraction of traction lines located in block 2.

The first drawback of the prototype is unreliable functioning of its invaginator - difficulties in introducing endoscopic tube 3 into seal 13 (see 42-53 lines of a.c. No.1522466). The invaginator is to be everted under tip 6, but during invagination the distal part of tube 3 becomes bared. It can be due both to lack of a gap between tube 3 and uneverted part of the invaginator and to a friable structure of the latter, which under the action of air pressure adheres to tube 3. Tube pleats formed during bending of the distal end also prevent free movement of the invaginator along tube 3. As a result the spring is unable to displace the invaginator to

tip 6. In addition, the invaginator's end 7, connected with two rings, ensures poor pressurization of cavity 14.

The second drawback of known endoscopes is that bending of its distal end is possible only until a definite number of flexures of an endoscopic tube. Its end is bent by rotating of two rollers each connected to its pair of traction lines. Springs, which comprise traction lines, on the distal end continue channels in the wall of cardan-joint rings. Ends of traction lines are soldered to the distal ring of the cardan mechanism for bending the distal end of the tube. Outward extraction of traction lines from the spring decreases gaps between cardan rings and forms a small radius of a flexure. Herewith, the distal cardan ring pulls the opposite traction line in distal direction, thus ensuring an increase of space between rings. Difference of lengths of big and small half-circumferences of the tube's bend is a product of « π » and diameter of an endoscopic tube. Japanese authors point out that when 3-4 loops are formed, the distal end of an endoscope is blocked, but biopsy forceps continue to function. This difference is explained by L. Aler formula

$$\frac{Q_1}{Q_2} = e^{\alpha f},$$

where: « Q_1 » - manual power realizing traction lines extraction; « Q_2 » - remaining from « Q_1 » power, attached to a distal cardan ring or cutters of biopsy forceps; « e » - basis of natural logarithm; « α » - traction line rotations in radians; « f » - friction index between a traction line and a spring. Under fixed values « Q_1 » and « f », value « Q_2 » depends on value « α », but for two consecutively connected traction lines of an endoscope the latter is twice as large as for one line of biopsy forceps.

The third drawback of the prototype are problems of its maintenance. For recurrent use an endoscope is washed, disinfected and sterilized. However, there are reported cases of infecting patients with AIDS and other infections after endoscopy. Preparation of the endoscope-prototype for work also includes its assembly. The number of detached parts of this endoscope amounts to 10, but its assembly takes about half an hour. Ergonomics of operating existing endoscopes also impede its mastering. Thus, the left hand holds the control bloc, switches its cocks, rotates handles, which bend and fix the distal end of the tube, but the right hand introduces the tube into the intestine.

It has been practically proved that if an endoscope has more than 3-4 loops, it is impossible to introduce biopsy forceps into it and take biopate. This is the fourth drawback of the prototype.

The objectives of the invention have been: - increase reliability of invagination of an endoscopic tube; - ensure bending of its distal end in flexuous channels; - make maintenance of an endoscope more convenient; - perform biopsy in flexuous channels. Implementation of these objectives will make colonoscopy available to any physician and make it easier for experienced endoscopists.

These objectives have been achieved by the fact that in the composition of an endoscope, which contains: - source of light; - source of pressure; - biopsy forceps; - an endoscopic tube with the control bloc and communication branch, at that the endoscopic tube contains

internally elements for light and image transmission, a channel gas/liquid, a biopsy channel, two pairs of springs with traction lines, which pairwise connect the mechanism for bending the distal end of the endoscopic tube with manual extractors of traction lines located in the control block, but externally a compressed spring placed on tubes distal end, the invaginator, the tip, a mobile seal, an anal dilator, additionally has been included:

- a new cylindrical invaginator, ensuring invagination of an endoscopic tube;
- a disposable cartridge connecting an invaginator with auxiliary elements;
- an endoscopic tube ensuring fixation of a cartridge;
- a mechanism for introduction of tube, ensuring concurrently with a cartridge insertion of a tube;
- a system of extractors-intractors of traction lines for bending the tube's end;
- a biopsy forceps' introduction and extraction system and traction line intensifier of biopsy forceps;
- a desk and pedal units of a control bloc of an endoscopic tube.

A compact hollow cylinder of the invaginator is formed of crumpled and tightly compressed in longitudinal and transverse directions short layers of different forms of an eversible thin-walled tube placed at different angles with the longitudinal axis of an endoscopic tube. The cylinder has recurrent narrowings of an external and widenings of its internal diameter.

A disposable sterile cartridge for invagination consists of a shell which has a projection at its proximal end, comprising: an invaginator; a compressed spring; its fixator; a spring distancer in which the distal seal of the endoscopic tube is located, which is joined to an unverted end of the invaginator; a condom of the distal part of the endoscopic tube fastened at the proximal end to a spring stop, but at the distal end - to the tip with elements for hermetic joining to the endoscopic tube, at that on the shell is located a proximal seal of the endoscopic tube with the anal dilator with the channel in its wall, but at the distal end of the shell the everted end of the invaginator is fastened. In addition to elements for air-tight joining to the endoscopic tube the tip may have a protective glass and a channel for glass washing.

A novel endoscopic tube is supplemented with: - internal transverse pleats of its external cover; - two air-ducts, the larger one has a lateral opening into the cavity of the proximal seal of the disposable cartridge for invagination, but the smaller - into the cavity of distal and proximal condoms; - areas for air-tight fixation of condoms' ends; - a proximal condom.

The mechanism for introduction of the endoscopic tube consists of the cylinder with two pistons, which are interconnected with distancers and an elastic tube. The cylinder is joined with the cartridge for invagination of the endoscopic tube. The cavity between pistons and the elastic tube is connected to the source of pressure or atmosphere (vacuum) through the cock. The cavity between the distal piston and the proximal seal of the endoscopic tube is connected to the source of vacuum or atmosphere (pressure) through the cock. The cocks can be placed in the pedals but the spring, which returns pistons to their home position can be located in the cavity between the proximal seal of the endoscopic tube and the distal piston.

00000 7450000

The system of extraction-intraction of traction lines ensuring management over the endoscopic tube's distal end, has a hydro-manual drive and creates additional power equal to a few grams at the distal end of traction lines. The system includes sources of pressure and vacuum connected to elastic tubes containing liquid and springs with traction lines. Tubes are fixed to springs with thread, but springs are made with steps. At the distal end springs are connected with traction lines. In the control bloc traction lines are attached to manual extractors-intractors of traction lines connected to elements ensuring synchronous feeding of vacuum into the cavity of a manually extracted traction line and feeding of pressure into the cavity of an introduced traction line. At the distal end of the tube and traction line a cylinder/piston unit can be placed or a segment of sylphone, the distal end of which is connected to a traction line. A manual extractor-intractor of traction line could be made in the manner of a rod, but the sources of pressure and vacuum – of a piston and cylinder, positioned on the rod. An element ensuring synchronous feeding of vacuum into the cavity of an extracted traction line and pressure into the cavity of an introduced traction line could be a gear mated with cogs of two rods. As each of two gears is coupled only with its pair of traction lines, the bending of the tube's end is performed in two stages. The cross-piece with a management lever, whose central part has a movable connection with the body of the desk node of control bloc, but ends are attached to four rods, pistons and cylinders, ensures simultaneous bending of the tube's end in any direction.

A system for intraction and extraction of biopsy forceps includes sources of pressure and vacuum, which are connected through a cock to the cavity of the biopsy channel, the entrance to which is sealed with a seal of biopsy forceps, at the distal end of which there is a piston of the biopsy channel. In addition the biopsy forceps have an intensifier of traction lines and contain a flexible hermetic tube, which is connected to sources of pressure and vacuum, but the distal end of the tube and traction lines finishes with a cylinder and a piston respectively. The unit piston/cylinder is possible to replace with a segment of sylphone, the distal end of which is connected to traction lines.

Cocks, feeding pressure into the invaginator and mechanism of tube's introduction have to be placed in the pedal node of the control bloc of the endoscopic tube, but the others - in the desk node.

The graphic materials illustrate the essence of invention, where on the fig. 1 is represented the endoscope with disposable cartridge for invagination, where: a - handle-shaped control bloc; b - distal part of endoscopic tube with mounted cartridge; c - longitudinal section of cartridge; d, e, f - enlarged fragments of fig.1c. On fig. 2 is shown the system of extraction-intraction of traction lines when the distal end of an endoscopic tube is in direct position, where: a - position of system elements comprised in control bloc; b - enlarged fragment of fig. 2a; c - distal part of tube with "bared" system elements (vertical arrows show the top-bottom of endoscopic tube); d – enlarged fragment of fig. 2c. On fig. 3 is represented the system of extraction-intraction of traction lines when the end of an endoscopic tube is bent downwards, where: a - position of elements contained in control bloc; b - enlarged fragment of fig. 3a; c - distal part of endoscopic tube with "bared" elements (horizontal arrows show the direction of traction lines motion); d, e - enlarged fragments of fig. 3c. On fig. 4 are represented: a - control bloc and design of new endoscope; b - cross-piece with lever, rods, pistons and cylinders; c – construction of a mechanism for introduction of endoscopic tube into cartridge; d - system of intraction and extraction of biopsy forceps; e – extraction and intraction system of biopsy forceps.

Specification of numerical markings of figs. 1-4 given at the end of the description is practically similar to graphic materials of the prototype. A novel endoscope includes endoscopic tube 3 with control bloc 2 and communication branch. Air-duct 15 and cock 17 positioned on control bloc 2 or in pedal, connect source of working pressure with opening 21 into the cavity of seal 13, which communicates with cavity 14 of shell 22. The distal part of shell 22 is commensurable in relation to length and diameter to unevverted part of invaginator 23, but the proximal part - to the compressed spring 10. Everted end 12 of invaginator 23 is connected to shell 22 by ring 16. Invaginator 23 has narrowings and widenings 24, as well as gap 25 with distal condom 26. Ends of distal 26 and proximal 27 condoms and corresponding to them places of tube 3 have areas 28 for interconnection and hermetization. Seal 29 on end 7 of invaginator 23 separates cavity 14 from cavity 25, which communicates with the intestinal cavity. A distancer 30 prevents deformation of seal 29 by spring 10. Ends of compressed spring 10 are based on distancer 30 and stop 11 at the end 28 of condom 26. Stop 11, in its turn, is positioned on the projection 31 of shell 22. The distal end of condom 26 ends with tip 6 with channels 32 for washing of protective glass 33 and blowing-up of intestines, as well as an element for connection to endoscopic tube 3. On the border of narrow and broad parts of shell 22 there is an area of intermediate diameter with indented elastic ring 34 for fixation of compressed spring 10. Channel 35 of anal dilator 19 is used for decompression of intestines during intubation. In the tube 3, besides the enumerated, there are elastic tubes 36, 37 comprising springs 38, 39 and traction lines 40, 41. Tubes 36, 37 are connected to springs 38, 39 with thread 42. Near mechanism 43 for bending the distal end of tube 3, ends of tubes 36, 37 are closed with plugs 44, which also connect springs 38, 39 with traction lines 40, 41. Proximal ends of tubes 36, 37 are connected with sources 45 of excess pressure and vacuum. Proximal ends of traction lines 40, 41 are connected with their manual extractors-intractors 46, but the latter - with element 47 which ensures synchronous feeding of vacuum into the cavity of traction line 40 which is being extracted and of pressure into the cavity of traction line 41 which is being introduced. Endoscopic tube 3 has internal pleats 48 of external cover, air-duct 49 with two openings 50 for vacuum fixation of condoms 26, 27 to tube 3 and also has removable sleeve gasket 51. Control bloc 2 has cock 52 of air-duct 49. Seal 13 is hermetically connected to mechanism 53 for introduction of endoscopic tube 3. Mechanism 53 for introduction of tube 3 is operated by pedal 54 but lever 55 realizes bending of tubes end. Cylinder 56, two pistons 57, distancers 58 and elastic tube 59 limit cavity 60, which is connected with source of pressure by means of cock in pedal 54. Cavity 61 comprises return spring 62 and is connected with vacuum by means of cock in pedal 54. Seal 64 and nut 65 are mounted on biopsy forceps 63, but piston 66 is positioned at their distal end. Seal for seal 64 and nut 65 is located at entry 67 to biopsy channel, which is positioned with cock 68 on control bloc 2. Sylphone 69, which serves as source of pressure and vacuum in pneumatic intensifier of traction line of biopsy forceps, can be combined with a handle of biopsy forceps 63.

00509377-000000

After the patient has been placed on an endoscopic table a cartridge is oiled and introduced into the rectum and its ampoule is examined as if with a rigid rectoscope. The pressure in cavity 14 is raised by pressing cock 17 thus freeing distancer 30 from coupling with fixator 34 and shell 22. Thereby spring 10 is released and it is possible to proceed with invagination of tube 3. Eversion of invaginator 23 and introduction of tube 3 into the colon occurs under working pressure in cavity 14 at the moments of pressing pedal 54. During endoscopy intestines are to be distended. Gas into intestines is constantly supplied through gas/liquid channel of tube 3 and through channel 32 of tip 6 thus preventing intestinal content of getting under protective glass 33. Gas evacuation from intestines occurs through channel 35 of anal dilator 19.

Bending of mechanism 43 is accomplished by means of excessive pressure and vacuum sources 45, manual extractors-intractors 46 of traction lines 40, 41 and by means of elements 47 which ensure feeding of vacuum in the cavity of tube 36 which comprises extracted traction line 40, and feeding of excessive pressure in the cavity of tube 37 containing introduced traction line 41. Due to vacuum elastic tube 36 and spring 38 are shortened. Considering, that their distal end is connected with traction line 40, this shortening relieves its manual extraction. Due to pressure in tube 37 the latter and spring 39 elongates towards executive mechanism 43 thus relieving manual intraction of traction line 41. Thread 42 twisted on tubes 36, 37, connects them with springs 38, 39. Thus, vacuum and pressure which shorten and elongate tubes 36, 37 and springs 38, 39 ensure application of powers to distal ends of traction lines 40 and 41; manual extraction and intraction of traction lines 40, 41 creates synchronous efforts on their proximal ends. Mechanism 43 of tube 3 is bent downwards by the above-mentioned method. During bending of mechanism 43 upwards all above enumerated elements are moved in opposite directions, but bending of mechanism 43 to the left and to the right is implemented by the second pair of traction lines which work similarly. In intermediate positions mechanism 43 is bent by interchangeable application of both pairs of traction lines. Element 47 made in the shape of a cross-piece with lever 55 ensures simultaneous bending of mechanism 43 in any direction.

As during colonoscopy tube 3 repeats all natural flexures of the colon its extubation must not be accelerated. Anal dilator 19 through which extubation is to be conducted eliminates unpleasant sensations caused by this process.

The most practical important version of the invention is a colonoscope with endoscopic tube 3 without biopsy channel. A disposable cartridge ensures an available to all and atraumatic transportation of tube 3 in the colon, condoms 26, 27 protect the patient from infections seated in endoscopic tube 3, but tube 3 - from getting contagious during endoscopy. Ergonomy of handling such colonoscope also makes it available to any physician: during endoscopy a physician in sedentary position, watches the screen, presses pedal cock 17 with one foot, pedal 54 with another, the right hand controls lever

For biopsy a cartridge with tip 6, without glass 33 is used. Having exhausted the possibility of manual insertion of forceps 63, it is necessary by means of seal 64 and nut 65 to hermetize entry 67 into the biopsy channel and connect it by means of cock 68 to the source of pressure. Further insertion of forceps 63 is performed by their manual intraction and due to pressure of liquid or gas on piston 66, but extraction – by switching cock 68 in the position «vacuum» and manual extraction of forceps 63. Due to location of source 69 of pressure and vacuum of traction line intensifier in the handle of forceps, taking of bioplate is made as previously - approach of rings ensures movement of the traction line inwards, but detachment - extraction of the traction line.

- 1 - eye-piece (fig. of the prototype only);
- 2 - control bloc with communication branch;
- 3 - endoscopic tube;
- 4 - everted part of invaginator (fig. of the prototype only);
- 5 - source of working pressure in cavity 14 (fig. of the prototype only);
- 6 - tip of endoscopic tube 3;
- 7 - non-everted end of invaginator 23;
- 8,9 - rings at the end 7 of invaginator (fig. of the prototype only);
- 10 - compressed spring;
- 11 - stop for spring 10;
- 12 - everted end of invaginator 23;
- 13 - proximal seal of tube 3;
- 14 - cavity of everted part 4 of invaginator 23;
- 15 - air-duct for feeding working pressure into cavity 14;
- 16 - ring, fixing end 12 of invaginator 23;
- 17 - cock of air-duct 15;
- 18 - manometer (fig. of the prototype only);
- 19 - anal dilator;
- 20 - rectum (fig. of the prototype only);
- 21 - air-duct 15 opening on tube 3;
- 22 - shell of cartridge for invagination;
- 23 - invaginator formed in a compact flexible cylinder;
- 24 - narrowings and widenings of cylinder of invaginator 23;
- 25 - gap (cavity) between cylinder of invaginator 23 and condom 26;
- 26 - distal condom of tube 3;
- 27 - proximal condom of tube 3;
- 28 - areas on tube 3 and at the ends of condoms 26, 27 for their hermetic connection.

- 29 - distal seal between tube 3 and end 7 of invaginator 23;
- 30 - distancer between spring 10 and invaginator 23 comprising seal 29;
- 31 - projection on shell 22 for stop 11;
- 32 - channel in tip 6;
- 33 - protective glass of tip 6;
- 34 - elastic ring, fixing spring 10 in compressed state;
- 35 - channel in anal dilator 19;
- 36 - lower elastic tube of extractor-intractor of traction lines;
- 37 - upper elastic tube of extractor-intractor of traction lines;
- 38 - lower spring of extractor-intractor of traction lines;
- 39 - upper spring of extractor-intractor of traction lines;
- 40 - lower traction line of extractor-intractor of traction lines;
- 41 - upper traction line of extractor-intractor of traction lines;
- 42 - thread fixing elastic tubes 36, 37 to springs 38, 39;
- 43 - mechanism for bending of distal end of tube 3;
- 44 - plug closing tubes 36, 37 and connecting springs 38, 39 with traction lines 40, 41;
- 45 - sources of pressure and vacuum;
- 46 - manual extractors-intractors of traction lines 40, 41;
- 47 - element for extraction-intraction of one or two pairs of traction lines;
- 48 - pleats of external cover of tube 3;
- 49 - air-duct into cavity of condoms 26, 27;
- 50 - distal and proximal openings of air-duct 49 on tube 3;
- 51 - sleeve gasket;
- 52 - air-duct 49 cock on control bloc 2;
- 53 - mechanism for insertion of endoscopic tube 3;
- 54 - pedal for switching on mechanism 53;
- 55 - lever of element 47, made in a shape of cross-piece;
- 56 - cylinder of mechanism 53;
- 57 - pistons of cylinder 56;
- 58 - distancers between pistons 57;
- 59 - elastic tube, attached to pistons 57;
- 60 - hermetic cavity, enclosed by elastic tube 59 and pistons 57;
- 61 - hermetic cavity, enclosed by seal 13 and distal piston 57;
- 62 - spring returning pistons 57 to home position;
- 63 - biopsy forceps;
- 64 - seal of entry 67 into biopsy channel;
- 65 - nut, fixing seal 64;
- 66 - piston of biopsy forceps;
- 67 - entry into biopsy channel;
- 68 - cock feeding pressure or vacuum into biopsy channel;
- 69 - source of pressure and vacuum connected with cavity of biopsy forceps 63.

1. An endoscope with a disposable cartridge for invagination of an endoscopic tube and biopsy in flexuous channels, incorporating: - a source of light; - sources of pressure and vacuum; - biopsy forceps; - an endoscopic tube with a control block and a communication branch containing inwardly light and image transmission elements, a liquid or gas feeding channel, a biopsy channel, two pairs of closely wound springs with traction lines which pairwise connect the mechanism for bending the distal end to manual extractors of traction lines located in the control block, but externally a spring mounted on the tube, an invaginator, a tip, a seal, an anal dilator, differs in that the invaginator is tightly set in layers in the shape of a cylinder placed with a gap to the endoscopic tube.
2. The endoscope as defined in claim 1 differs in that the invaginator in the form of a compact hollow cylinder is formed of different forms short layers of a thin-walled eversible tube compressed in longitudinal and transverse directions arranged at different angles and has narrowings of an external and widenings of internal diameters.
3. The endoscope as defined in claim 1 or 2 differs in that it is supplied with a disposable cartridge consisting of a shell with a projection at proximal end in which are located the invaginator, a spring, a spring fixator, a spring distancer in which a distal seal of the endoscopic tube fastened at the uneverted end of the invaginator is placed, a condom of the distal part of the endoscopic tube connected to a spring stop and tip with elements for hermetic fastening to the endoscopic tube, at that the proximal seal of the endoscopic tube with an anal dilator having a channel in the wall is located at the shell, but the everted end of the invaginator is fastened at the distal end of shell.
4. The endoscope as defined in claim 3 differs in that the endoscopic tube has transverse pleats of its external cover turned inwards and the areas for air-tight fixation of condoms' ends, as well as two air-ducts with cocks, whereof the larger one communicates through its lateral opening with the cavity of the proximal seal of the endoscopic tube, but the smaller - with the condoms' cavity.
5. The endoscope as defined in any preceding claim differs in that the proximal end of the cartridge for invagination joins the endoscopic tube introduction mechanism made in the shape of a cylinder with two pistons which are interconnected with distancers and the elastic tube, but the cavity between them is connected to the pressure and vacuum sources, at that the cavity between the proximal seal of the endoscopic tube and the distal piston comprises the spring, which returns the pistons to their home position and is connected to vacuum and pressure sources.
6. The endoscope as defined in any preceding claim differs in that it is supplied with an extraction-intracation system of traction lines with hydro-manual drive for controlling the distal end of the endoscopic tube, including pressure and vacuum sources which are linked to elastic tubes cavities comprising liquid and springs with traction lines, at that tubes are fixed to springs with a thread but the springs are made with steps and at the distal end are joined with traction lines, connected in control block with manual extractors-intracators of traction lines, which, in their turn, are joined with elements for synchronous vacuum feeding into the cavity of the manually extracted traction line and excess pressure into the cavity of the introduced traction line.

09/509377, 08/0800

- 017-8-83 40 1DE
7. The endoscope as defined in claim 6 differs in that the extractors-intractors of traction lines contain rods with pistons and cylinders positioned on them and the element connected with rods for synchronous vacuum creating in the cavity of the extracted traction line and pressure in the cavity of the introduced traction line, at that this element is made in the shape of gear or a cross-piece connected with a control lever.
 8. The endoscope as defined in claims 6, 7 differs in that the distal ends of the tubes and the traction lines terminates with a cylinder and a piston accordingly or the tubes' distal ends terminates with an elastic element, for instance a sylphone, but the traction lines are connected with the sylphone's distal end.
 9. The endoscope as defined in any preceding claim differs in that it is supplied with a system for introduction and extraction of biopsy forceps which includes pressure and vacuum sources connected through a cock to the cavity of the biopsy channel, the entrance to which is hermetized by a biopsy forceps seal, but their distal end has a biopsy channel piston, at that the biopsy forceps have a traction line intensifier and include a flexible hermetic tube the cavity of which is connected to a pressure and vacuum source, but the distal ends of the traction line and the tube terminates with a piston and a cylinder accordingly or the tube terminates with an elastic element, for instance, a sylphone, but the traction line is connected to its distal end.
 10. The endoscope as defined in any preceding claim differs in that a control block of the endoscopic tube is made in the shape of desk and pedal units.

0550377.002800

THE 2000

THE 2000





Fig. 1




Fig. 2





Fig. 3

Fig. 4

Please type a plus sign (+) inside this box → 

Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63) <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	Attorney Docket Number	
	First Named Inventor	
	Sergey Matusov	
	COMPLETE IF KNOWN	
	Application Number	/
Filing Date		
Group Art Unit		
Examiner Name		

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Endoscope with single-use cartridge for the invagination of endoscopic tube

the specification of which (Title of the Invention)

☐ is attached hereto
OR

☒ was filed on (MM/DD/YYYY) **10/02/1998** as United States Application Number or PCT International

Application Number **PCT/LV98/00006** and was amended on (MM/DD/YYYY) **01/10/2000** (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(e) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
P-97-190	LATVIA	10/03/1997	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
P-98-188	LATVIA	09/23/1998	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
I.c. 1522466	USSR	08/21/1978	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 115(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

(Page 1 of 2)

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application(s) designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent
Number

Parent Filing Date
(MM/DD/YYYY)

Parent Patent Number
(if applicable)

PCT/LV 98/00006

10/02/1998

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☐ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name

Registration
Number

Name

Registration
Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number
or Bar Code Label

OR ☒ Correspondence address below

Name Sergey Matasov
Address Ranka dambis 7/1 - 55
Address
City Riga State ZIP LV1048
Country LATVIA Telephone +371 7601489 Fax +371 7601489

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

☒ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))

Family Name or Surname

Sergey

Matasov

Inventor's
Signature

Date 03/20/2000

Residence: City

Riga

State

Country

Latvia

Citizenship

Post Office Address

Slokas 33

Post Office Address

Riga

State

ZIP

LV1048

Country

LATVIA

☐ Additional inventors are being named on the supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto